

Vacuum Sweeper:



DISA-CLEAN 130

The new generation Road Sweeper from DISAB is designed with a combination of traditional broom technology and high vacuum technology which makes it possible to clean streets/road surfaces completely dust free.

DISA-CLEAN technology uses traditional brooms and side brushes, however capsuled within vacuum aspiration which eliminates all dusting around the brooms and brushes.

Directly after the brush system there is a specially designed vacuum nozzle. This nozzle covers the full width of the truck and vacuums the surface with suction power up to 1600 kg. This enables the Disa-clean to also suck the finest particles (PM10) which are normally left behind after conventional sweeping methods.

Crucially Disa-clean uses NO WATER in its cleaning process. This means dust and particles are not stuck down to the floor during the process like a conventional sweeper.

Material and dust is sucked into the special designed 4-step separator where everything is separated and the exhaust air is cleaned through a 2-step filter system designed to separate PM 10 particles.

DISAB GmbH



THESE ARE RESULTS YOU CAN SEE!

Results in industry:



Results in the City



WWW.DISAB.COM

+44 (0)1737 246 649

DISAB UK, ALMA HOUSE ALMA ROAD, REIGATE, SURREY RHZ DAX

DISAB VACUUM TECHNOLOGY AB

Âkermans väg 24
← +46 (0) 413 55 43 00
SE- 241 23 ESLÖV
→ +46 (0) 413 55 43 01

⋈ mobile@disab.com ## www.disab.com

 industrial@disab.com # www.disab.com

DISAB GmbH ம் Mühlenstr. 25

klaus.klein@disab.com

www.disab.com



Versatile unit for the Contractor

As the unit is using high vacuum technology it can also be used as a traditional vacuum loader for heavy vacuum cleaning within the process industry.

This means a large capacity hose can be connected to the unit and used with long lengths of operator hose or to be connected to fixed centralized pipework systems.



DISAB VACUUM TECHNOLOGY AB

Åkermans väg 24
L +46 (0) 413 55 43 00
SE- 241 23 ESLÖV
→ +46 (0) 413 55 43 01



Main components/Technical basic data DISA-CLEAN 130

DISA-CLEAN 130 is designed to be mounted onto a truck chassis. Preferable right-hand drive for right-hand traffic roads. Recommended chassis is Volvo FE 240 which is quoted upon request.







Truck chassis Volvo FE 240 4*2 class Euro 6

Medium chassis height with rear air suspension

Chassis height medium - approx. 900 mm above ground level

Day cab (L=1.6 m)

Euro 4 SCR Selective Catalytic Reduction

Euro 4 Engine emission control

Diesel engine, 7 liter, 240 hp, 920 Nm

Engine brake with Exhaust Press Governor, EPG

Overdrive manual 9 speed ZF gearbox, 1200 Nm

Single plate clutch, plate diameter 395 mm

Wheelbase 4300 mm

Front axle load 8.0 tons

Front suspension type, air

Rear air suspension, 2 bellows


Rear single reduction solo axle - axle load 13 tons, GCW 44 tons

Rear axle ratio 6.17

Rear axle load 13 tons

Rear suspension type, air

Without rear stabilizer



WWW.DISAB.COM

+44 (0)1737 246 649

DISAB UK, ALMA HOUSE ALMA ROAD, REIGATE, SURREY RHZ DAX

a www.disab.com




Auxilliary engine (step III B)

Model: Turbo 4-cylinder Perkins (step III B

Power: 129 kW ISO3046

Diesel tank: integrated with truck tank

Electrical system: 24 VDC



Vacuum pump:


System: **Roots Blower** Airflow: 8000 m³/h 400 mbar Vacuum



Control system:

All Controls are PLC based with Touchscreen menus for optimal control and handling.











+44 (0)1737 246 649

DISAB UK, ALMA HOUSE ALMA ROAD, REIGATE, SURREY RHZ DAX

WWW.DISAB.COM

industrial@disab.com

www.disab.com



Filter system:

Type: Filter cartridges of polyester

Membrane (coating): PTFE (Teflon)


M (= particles ≥ 0,2µm are separated Filter class (IEC EN 60335-2-

by 99,9%


Filter cleaning system: Aut. Roto-pulse

Safety/Back-up filter: Filter cartridge class F7/M











Tank volume:

5 m³ (discharged by tipping - hydraulic cylinder)

Rear hose connect: 1 x dia. 203/152 mm

Vacuum nozzle & Aspirated capsuled brooms & side brush

Sweeping width: Main brooms & nozzle 2500 mm

+ optional side brush left 300mm + optional side brush right 300mm= total sweeping width 2800 mm/3100mm.

Function: hydraulic drive with pneumatic vertical control completely dust free.

Miscellaneous:

Working/Operating lighting included

4 pcs Cameras (rear and nozzles) incl. 7" colour screen (splitscreen) not included

4 pcs Flash lights not included

Operating speed: Up t0 15 km/hr. Capacity: - 37500 m²/hr

Cleaning width: 2500-2800 mm (3100 mm)

Approx. 5 tonnes (5 m3 tank body) Pay load: Noise level: Approx. 85 dB(A) at 5 m distance

Height=3,25 m, Length=7,65 m, Width=2,5 m Measurements:

18 tonnes Total weight:



WWW.DISAB.COM


+44 (0)1737 246 649

DISAB UK, ALMA HOUSE ALMA ROAD, REIGATE, SURREY RHZ DAX





OPTIONS

1.A Option: Side brush right side.



1.B Option: Side brush left side





WWW.DISAB.COM

+44 (0)1737 246 649

DISAB UK, ALMA HOUSE ALMA ROAD, REIGATE, SURREY RHZ DAX

DISAB GmbH